

## Applications

### 7W LED JDR LAMP

- Accent lighting
- Display lighting
- Recessed lighting
- Track lighting



## Features

- 7W LED PAR16 designed as 50W halogen PAR16 replacement
- Dimmable 10~100% \*
- 25,000hrs life @ 70% lumens maintenance
- UL approved for Dry and Damp locations
- Mercury free and RoHS compliant
- UV and IR free



## Order Code

Product Code	Nom. Watts	Volt s	Description	Bulb Type	Base	Rated Avg. Life (Hrs.) <sup>1</sup>	Approx. Lumens <sup>2</sup>	CRI	Color Temp. (Kelvin)	Power Factor	MOL (mm)
EJDR720WW	7	120	120V LED Dimmable JDR 40° Warm White	PAR16	E26	25,000	450	80	2700	0.95	53
EJDR720W	7	120	120V LED Dimmable JDR 40° White	PAR16	E26	25,000	480	78	5000	0.95	53

1. Rated average life based on engineering testing and probability analysis.
2. Photometric testing consistent with IES LM-79.

\* Designed for "Leading Edge" TRIAC dimming systems. Refer to <http://www.everbrightlights.com/dimmerlist.html> to find up to date dimmers compatibility information.

## Notes

- This lamp is not intended for use with emergency exit fixtures or emergency lights.
- Turn off power before changing the lamp.
- Working temperature -20°C~40°C
- This lamp is not suitable for totally enclosed fixtures or insulated air tight recessed down lights
- NOT FOR USE WHERE EXPOSED TO THE WEATHER
- Risk of Electrical Shock - Do not use directly exposed to the water
- Suitable for damp locations
- This device complies with Part 15 of the FCC rules and has been tested and found to comply with limits for a Class B digital device. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

## Dimensions

Unit: mm

